


PTH49AIRS
500 lbs [225 kg]




**THE ORIGINAL
 & TRUSTED NAME
 IN VACUUM LIFTING
 EQUIPMENT**

908 West Main - P.O. Box 368
 Laurel, Montana 59044 U.S.A.
 406.628.8231 (phone)
 406.628.8354 (fax)

800.548.7341
www.WPG.com

AIR-POWERED TILTER 500
WITH INTEGRATED HOIST

Designed with an integrated hoist, this Powr-Grip® vacuum lifter uses compressed air in production facilities to lift loads and provide effortless 90° tilt.



Standard Pad Spread	20½" x 37½" [523 x 955 mm]
Number / Size of Pads	4 / 9" [23 cm] diameter
Load Capacity	500 lbs [225 kg]
Unit Weight	247 lbs [112 kg]
Standard Operating Power	Compressed air, 12.5 SCFM [354 liters/minute] @ 80 psi [552 kPa]
Apply	2 seconds (approximately)
Release	1 second (approximately)
Load Movement	Power tilt, 90° between upright and flat Powered vertical travel, 48" [122 cm]
Time for 90° Tilt	8 seconds (approximately)
Tilt Duty	Continuous
Standard Features	Vacuum gauge Vacuum reserve tank Vacuum line filter Spring-mounted pads Blow-off for quick release
Available Options	Vacuum loss warning buzzer (EO3VLW) Individual pad shutoffs (CM1COWB) Alternative frame dimensions and configurations
Design Standards: (See www.WPG.com for more information.)	ASME B30.20 - 2006 (BTH-1 Design Category "B", Service Class "0")