

RAM® EQUIPMENT MOUNTING SYSTEMS



Wood's Powr-Grip® is pleased to offer Vacuum Mounting Cups for use with RAM® Mount Accessories: Together they create the most reliable and effective mounting systems available for holding GPS units, smart phones, tablets, video cameras and just about any kind of equipment imaginable! It's easy to mount your device in a vehicle or on any smooth, nonporous surface.



TL3PB1

Specifications:
 Model: TL3PB1
 Stock#: 91160
 Mount: Black Metal
 Ball: 1" [2.5 cm]
 Vacuum Pad: Concave, 3" [8 cm] diameter (model TL3)
 Pad Radius: 4" [10 cm]
 Capacity: 15 lbs [7 kg]
 Includes pad protector.



LJ45PB1

Specifications:
 Model: LJ45PB1
 Stock#: 91255
 Mount: Black Polycarbonate
 Ball: 1" [2.5 cm]
 Vacuum Pad: Concave, 4-1/2" [11 cm] diameter (model LJ45)
 Pad Radius: 12" [30 cm]
 Capacity: 40 lbs [18 kg]
 Includes pad protector.



TL6PB1

Specifications:
 Model: TL6PB1
 Stock#: 91390
 Mount: Black Polycarbonate
 Ball: 1" [2.5 cm]
 Vacuum Pad: Concave, 6" [15 cm] diameter (model TL6)
 Pad Radius: 12" [30 cm]
 Capacity: 70 lbs [32 kg]
 Includes pad protector.

RAM® Mount Accessories:

- 1-3/4" [4.5 cm] double socket arm (RAM-B-201U-A)
- Universal X-Grip™ Cell Phone Holder (RAM-HOL-UN7BU)

RAM® Mount Accessories:

- 1-3/4" [4.5 cm] double socket arm (RAM-B-201U-A)
- 3" [7.5 cm] double socket arm (RAM-B-201U)
- Universal X-Grip™ Cell Phone Holder (RAM-HOL-UN7BU)

RAM® Mount Accessories:

- 1-3/4" [4.5 cm] double socket arm (RAM-B-201U-A)
- 3" [7.5 cm] double socket arm (RAM-B-201U)
- 5-1/4" [13.5 cm] double socket arm (RAM-B-201U-C)
- Universal X-Grip™ Cell Phone Holder (RAM-HOL-UN7BU)

THE ORIGINAL
 & TRUSTED NAME
 IN VACUUM LIFTING
 EQUIPMENT



RAM-HOL-AQ7-2U

RAM® Aqua Box® Sealed Cell Phone Enclosure

- Stock#: 60069
- Interior Dimensions: 5.38" (L) x 2.8" (W) x 0.55" (D)
 - Construction: High-strength composite with PVC windows
 - Compatible with Ram® Diamond Base with 1" Ball and other mounting accessories.



RAM-HOL-UN7BU

RAM® Universal X-Grip™ Cell Phone Holder

- Stock#: 60079
- Compatible Device Dimensions:
 - Minimum Width = 0.875" [22 mm] (Note: corresponding Minimum Length = 4" [102 mm])
 - Maximum Width = 3.25" [82 mm]
 - Recommended Depth ≤ 0.875" [22 mm]
 - Ball Size: 1" [2.5 cm] Rubber Ball Mount.



RAM-B-289U

RAM® Triple 1" Ball Base

- Stock#: 60078
- Three 1" [2.5 cm] rubber balls enable you to employ multiple Powr-Grip® Mounting Cups.
 - Ideal for mounting a wide variety of equipment.
 - Also compatible with RAM® Double Socket Arms.



908 West Main - P.O. Box 368
 Laurel, Montana 59044 U.S.A.
 406.628.8231 (phone)
 406.628.8354 (fax)

800.548.7341
 www.WPG.com



Products are manufactured under an ISO 9001 quality management system

Wood's Powr-Grip products are sold through authorized dealers.



RAM-B-231ZU

RAM® Handlebar Mount with 1" Ball

Stock#: 60071AM

- Compatible Handlebar Sizes: 0.5" [1.3 cm] to 1.25" [3.1 cm] diameter
- Ball Size: 1" [2.5 cm] diameter



RAM-B-201U-A

RAM® 1 1/4" Marine Grade Aluminum Double Socket Arm

Stock#: 60061

- Effective Length: Approx 1 1/4" [4.5 cm] from socket center to socket center
- Compatible Ball Size: 1" [2.5 cm] diameter



RAM-B-201U

RAM® 3" Marine Grade Aluminum Double Socket Arm

Stock#: 60060

- Effective Length: Approx 3" [7.5 cm] from socket center to socket center
- Compatible Ball Size: 1" [2.5 cm] diameter



RAM-B-201U-C

RAM® 5 1/4" Marine Grade Aluminum Double Socket Arm

Stock#: 60062

- Effective Length: Approx 5 1/4" [13.5 cm] from socket center to socket center
- Compatible Ball Size: 1" [2.5 cm] diameter



RAP-B-201-1U

RAM® 2" Lightweight Composite Double Socket Arm

Stock#: 60060AB

- Effective Length: Approx 2" [5 cm] from socket center to socket center
- Compatible Ball Size: 1" [2.5 cm] diameter



RAP-B-201U-A

RAM® 2" Heavy-Duty Composite Double Socket Arm

Stock#: 60060AZ

- Effective Length: Approx 2" [5 cm] from socket center to socket center
- Compatible Ball Size: 1" [2.5 cm] diameter



RAP-B-201U

RAM® 3" Heavy-Duty Composite Double Socket Arm

Stock#: 60060AM

- Effective Length: Approx 3" [7.5 cm] from socket center to socket center
- Compatible Ball Size: 1" [2.5 cm] diameter



RAM-WPG-FAA

1/4-20 x 1/4" NPS Adapter Kit

Stock#: 60072AZ

- Two adapter fittings with 1/4-20 female thread on one end and 1/4" NPS female thread on the other end.
- Two 1/4-20 thread socket head screws.
- Used to attach RAM® Flexible Arms to Powr-Grip's Vacuum Mounting Cups or to various mounting accessories.



RAM-A-336U

RAM® 9/16" Ball with 1/4-20 Tap

Stock#: 60077

- 9/16" [1.4 cm] rubber ball with spacer and 1/4-20 tapped threads.
- Ideal for mounting a wide variety of equipment.
- Rubber ball mounts on RAM® Double Socket Arms.
- Also used to make Powr-Grip's 1/4-20 Stud Mounting Cups compatible with RAM® Double Socket Arms.



RAM-B-337U

RAM® 1" Ball with 1/4-20 Tap

Stock#: 60063

- 1" [2.5 cm] rubber ball with spacer and 1/4-20 tapped threads.
- Ideal for mounting a wide variety of equipment.
- Rubber ball mounts on RAM® Double Socket Arms.
- Also used to make Powr-Grip's 1/4-20 Stud Mounting Cups compatible with RAM® Double Socket Arms.



RAM-WPG-PB1CP

1" Ball with 1/4-20 Stud & Contact Plate

Stock#: 60071

- 1" [2.5 cm] polycarbonate ball with spacer, 1/4-20 threaded stud and contact plate.
- Ideal for mounting camcorders, cameras, scopes and many other types of equipment.
- Contact plate prevents damage to equipment at mounting point.
- Poly ball mounts on RAM® Double Socket Arms.



RAM-WPG-PB1

1" Ball with 1/4-20 Stud

Stock#: 60073

- 1" [2.5 cm] polycarbonate ball with spacer and 1/4-20 threaded stud.
- Ideal for mounting a wide variety of equipment that does not require a contact plate.
- Poly ball mounts on RAM® Double Socket Arms.



RAM-WPG-PB2

1" Ball with Spacer & 1/4-20 Tap
Stock#: 60073

- 1" [2.5 cm] polycarbonate ball with long spacer and 1/4-20 tapped threads.
- Steel hex-shaped spacer for secure attachment.
- Ideal for mounting a wide variety of equipment.
- Poly ball mounts on RAM® Double Socket Arms.



RAM-B-238U

RAM® Diamond Base with 1" Ball
Stock#: 60071AZ

- Base Dimensions: 2.43" [6.17 cm] x 1.31" [3.33 cm].
- Hole Spacing: 1.912" [4.856 cm] from center to center.
- Ball Size: 1" [2.5 cm] diameter.



RAM-PF-585-12

RAM® 12" Flexible Arm
Stock#: 60067

- Effective Length: Approx 12" [30.5 cm] when straightened
- Threads: Male 1/4" NPS



RAM-PF-585-6

RAM® 6" Flexible Arm
Stock#: 60066

- Effective Length: Approx 6" [15 cm] when straightened
- Threads: Male 1/4" NPS



CELL PHONE VACUUM MOUNT W/ RAM® X-GRIP™ HEAD (TL3PB1SXCEL)

Stock#: 91161

- Vacuum Pad: Concave, 3" [8 cm] diameter (model TL3)
- Pad Radius: 4" [10 cm]
- Effective Arm Length: Approx 2" [5 cm] from socket center to socket center
- Ball Joint Size: 1" [2.5 cm] diameter
- Compatible Device Dimensions for RAM® X-Grip™ :
Minimum Width = 0.875" [22 mm] (Note: corresponding Minimum Length = 4" [10 cm])
Maximum Width = 3.25" [82 mm]
Recommended Depth ≤ 0.875" [22 mm]



PHABLET VACUUM MOUNT W/RAM® X-GRIP™ HEAD (TL3PB1SXCEL45)

Stock#:91162

- Vacuum Pad: Concave, 3" [8 cm] diameter (model TL3)
- Pad Radius: 4" [10 cm]
- Effective Arm Length: Approx 2" [5 cm] from socket center to socket center
- Ball Joint Size: 1" [2.5 cm] diameter
- Device Dimensions to Fit RAM® X-Grip™ Phablet:
Minimum Width = 1.75" [4.45 cm]
Maximum Width = 4.5" [11.4 cm]
Recommended Depth ≤ 0.875" [22 mm]



7" TABLET VACUUM MOUNT W/RAM® X-GRIP™ HEAD (TL3PB1SXCEL7)

Stock#:91163

- Vacuum Pad: Concave, 3" [8 cm] diameter (model TL3)
- Pad Radius: 4" [10 cm]
- Effective Arm Length: Approx 2" [5 cm] from socket center to socket center
- Ball Joint Size: 1" [2.5 cm] diameter
- Device Dimensions to Fit RAM® X-Grip™ 7" Tablet Holder:
Minimum Width = 2.25" [5.71 cm]
Maximum Width = 5.75" [14.6 cm]
Recommended Depth ≤ 0.875" [22 mm]



10" TABLET VACUUM MOUNT W/RAM® X-GRIP™ HEAD (LJ45PB1SXCEL10)

Stock#: 91261

- Vacuum Pad: Concave, 4½" [11 cm] diameter (model LJ45)
- Pad Radius: 12" [30 cm]
- Effective Arm Length: Approx 2" [5 cm] from socket center to socket center
- Ball Joint Size: 1" [2.5 cm] diameter
- Device Dimensions to Fit RAM® X-Grip™ 10" Tablet Holder:
Minimum Width = 6.25" [15.87 cm]
Maximum Width = 8.1" [20.57 cm]
Recommended Depth ≤ 0.875" [22 mm]

State laws vary regarding in-vehicle mounting and use of electronic devices. Check with local authorities to determine applicable laws in your location.