





WOOD'S POWR-GRIP[®] MANUAL ROTATOR 4200 WITH DC3 DUAL VACUUM SYSTEM

MR2411LDC3S
4200 lbs [1905 kg]



Employing state-of-the-art technology, *Intelli-Grip*[®] automatically monitors vacuum and power systems to:

- Maximize productivity
- Help reduce human error
- Simplify maintenance and repairs
- Protect employees and property from harm



	MR2411LDC3S
Maximum Load Capacity	4200 lbs [1905 kg]
Intelli-Grip[®] Technology	Automatic self-testing ensures lifter is ready for use, every lift. Color display provides critically relevant information at a glance. Anticipates threats and alerts operator beforehand with clearly visible and audible warnings. Continuously monitors battery and prevents lifter from attaching to loads if energy is hazardously low. Multiple alarm levels plainly identify the severity of hazards.
Load Movement	Manual rotation, 360° edgewise, with manual break (infinite load positioning)
Standard Operating Power	12 volts DC, 12 amps
Standard Features	Intelli-Grip [®] technology Dual vacuum system Multi-position lift shackle Battery and charger Battery energy gauge Low vacuum strobe light Low vacuum/power loss warning buzzer with back-up battery Green lift light Remote control system Vacuum gauges Vacuum reserve tanks Vacuum line filters Removable lift bar extension Removable pad frame sections Spring-mounted vacuum pads Blow-off for quick release Two-action, push-button release Reusable shipping crate
Available Options	Custom pad frame sizes and capacities (special order) Alternative pad compounds, including ones for low-marking, temperature resistant and coated surface applications (special order) Available for lease
Dual Vacuum System	Features two completely independent vacuum circuits. Provides vacuum system redundancy. Limits possibility of a catastrophic failure. Reduces chance of harm to personnel or equipment.
Lifter Weight	1100 lbs [499 kg]
Standard Pad Spread	Maximum: 65" x 194" [165 cm x 493 cm] Minimum: 32½" x 90" [83 cm x 290 cm]
Number / Size of Pads	24 / 11" [28 cm] diameter, lipped vacuum pads
Design Standards	ASME B30.20 (BTH-1 Design Category "B", Service Class "0") CE (See www.WPG.com for more information.)

Based on product information at time of publication. Environmental conditions can affect product performance and longevity; consult the product instructions on WPG.com or contact a Technical Sales Representative for more information.



**THE ORIGINAL
& TRUSTED NAME
IN VACUUM LIFTING
EQUIPMENT**

800.548.7341
WPG.com

908 West Main - P.O. Box 368
Laurel, Montana 59044 U.S.A.
406.628.8231 (phone)
406.628.8354 (fax)

